






## A100 Audio Gateway

The A100 Audio Gateway provides synchronized audio with video, two-way audio with broadcasting, glass break detection, and more.



## Get Intelligent Audio Analytics

The A100 introduces intelligent audio analytics to Rhombus and doubles as a primary connection hub for Rhombus Sensors, delivering greater insight flexibility. Pair with any Rhombus camera to capture audio with synchronized video, and receive real-time alerts triggered by abnormal audio events. With its built-in speaker and microphone, two-way communication is a breeze, and you can even connect external audio devices for broadcasting messages at scale.

-  Starting at \$349 (MSRP USD)
-  Capture synchronized audio
-  Broadcast pre-recorded or live messages
-  Real-time alerts based on audio triggers
-  Backed by a 2-year warranty



## A100 Specs

**Dimensions:** 118mm (4.64in) x 50.8mm (2in)

**Format:** WebM (OPUS), MP4 (AAC)

**Ethernet:** 10/100 Mbps, MDI/MDX Auto Sensing

**Power-over-Ethernet:** Standard 802.3af for one-cable installation

**Power Consumption:** Max 13 watts

**Onboard Storage:** 64GB

**Internal Microphone:** Omni-Directional (94dB SPL @ 1KHz / 100Hz – 10,000Hz);

**Internal Speaker:** 82.5dB +/- 3dB

**External Audio:** 3.5mm microphone input jack; 3.5mm speaker output jack

**Wireless:** Bluetooth

**Baseline, steady state:** 2— 10 Kbps

**Live streaming:** 52 Kbps

**Temperature:** 10° to 50°C (50° to 122°F).

**CE, FCC, NDAA, TAA Compliant**